

DO NOT USE FOR FLIGHT

B-52 Driver



FLIGHT MANUAL

PART III - Normal Procedures

Captain Sim is not affiliated with any entity mentioned or pictured in this document.
All trademarks are the property of their respective owners.

DO NOT USE FOR FLIGHT

ABOUT THIS MANUAL

VERSION: 13 DECEMBER, 2010

WARNING: THIS MANUAL IS DESIGNED FOR MICROSOFT® FSX USE ONLY. DO NOT USE FOR FLIGHT.

The 'B-52 Driver' FLIGHT MANUAL is organized into three Parts.
Each Part is provided as a separate Acrobat® PDF document:

- **Part I – User's Manual**
- **Part II – Aircraft Systems**
- **Part III – Normal Procedures** - this document.


FOR GENERAL INFORMATION ON THE 'B-52 DRIVER' PRODUCT PLEASE USE WWW.CAPTAINSIM.COM .
THIS MANUAL PROVIDES ADDITIONAL INFORMATION ONLY, WHICH IS NOT AVAILABLE ON THE WEB SITE.

SECTION I

NORMAL PROCEDURES

This section contains text, performance data, flight profiles and an amplified checklist. The text is divided into primary paragraphs which form the phases of a normal flight. Most of these paragraphs are followed by an amplified checklist for the particular phase of the flight. The amplified checklist is presented in a chronological form that will enable the pilot to complete his inspection, checks, and operation of the aircraft in an expedient yet thorough manner. The amplified checklist describes in detail the steps to be completed. The terms "As required," "As desired," "Climatic," and "Cross-checked" as used in the checklist indicates equipment operation or settings which may vary according to prevailing conditions. In practice, the response to these items will be the required switch or control position or actual indicator reading. The amplified checklist has also been designed to accommodate the production of the abbreviated checklist to be used during aircraft operation.

This manual based on original B-52 flight manual and adapted for a single-pilot FSX environment.

DO NOT USE FOR FLIGHT**PREFLIGHT CHECK****EXTERIOR INSPECTION****NOTE**

- Because of the size and complexity of the aircraft, the detailed inspection will have been completed by qualified ground crew personnel. The flight crew exterior inspection is an inspection of general aircraft condition. This inspection is based on the assumption that the flight crew is merely accepting the aircraft for flight with emphasis on the items that affect the safety of flight. During the inspection, emphasis will be directed toward a checking for hydraulic leaks, fuel leaks, and general condition.

DO NOT USE FOR FLIGHT**INTERIOR INSPECTION CHECKLIST (LEFT SEAT)**

- | | | |
|----|----------------------------------|------------------|
| 1. | Autopilot Servos Cutout Switches | OFF |
| 2. | Antiskid Switch | ON, guard closed |
| 3. | Mach Indicator Switch | ON |

NOTE

- The mach indicator will be unreliable and needle oscillation may occur until sufficient pitot pressure is attained during takeoff. The pilot should expect and disregard this oscillation.

- | | | |
|-----|------------------------------------|-----------------|
| 4. | Hydraulic Standby Pump Switches | OFF |
| 5. | Rudder/Elevator Hydraulic Switches | OFF |
| 6. | Clock | Checked and set |
| 7. | Anti-Icing Switches | OFF |
| 8. | Yaw SAS Switch | DISENGAGE |
| 9. | Airbrake Lever | OFF |
| 10. | Crosswind Crab Knob & Indicator | Zero |

INTERIOR INSPECTION CHECKLIST (RIGHT SEAT)

- | | | |
|-----|---|-----------------|
| 1. | Battery Switch | OFF |
| 2. | Engine Starter Switches | OFF |
| 3. | Frequency And Voltmeter Selector Switch | CENTRAL BUS TIE |
| 4. | Generator Drive Decoupler Switches | Checked in NORM |
| 5. | Clock | Checked and set |
| 6. | All Fuel System Switches | OFF and CLOSED |
| 7. | Landing Gear Lever | GEAR DOWN |
| 8. | Throttles | CLOSED |
| 9. | Drag Chute Lever | Checked |
| 10. | Wing Flap Lever | OFF |
| 11. | Terrain Display Mode Selector Switch | OFF |

BEFORE STARTING ENGINES**BEFORE STARTING ENGINES CHECKLIST**

- | | | |
|----|--------------------|-----|
| 1. | Gyro Power Switch | ON |
| 2. | Battery Switch | ON |
| 3. | Generator Switches | OFF |
- Momentarily position generator switches to OFF and check generator circuit breakers open and bus tie circuit breakers closed.
- | | | |
|----|---|-------------------|
| 4. | External Power Switch | ON (if available) |
| 5. | Oxygen Quantity | Checked |
| 6. | Fuel Quantity Check | Completed |
| 7. | Navigation Lights | ON |
| 8. | Radios | CHECK |
| 9. | NAV equipment | CHECK as follows: |
| | (1) Nav Mode Select Switch - VOR | |
| | (2) Check that bearing pointer points to the station. | |
| | (3) Rotate course set knob and check that TO changes to FROM indication | |
| | (a) DME alive. | |
- | | | |
|-----|---|--------------|
| 10. | Elevator & Rudder | Checked |
| | a. Rudder/Elevator Hydraulic Switches - ON, lights out; Check main and aux hydraulic system lights out. | |
| | b. Elevator Check: | |
| (1) | Control Column | Full forward |
| | Ground observer reports position of elevators. | |
| (2) | Control Column | Full back |
| | Ground observer reports position of elevators. | |
| | c. Rudder & Rudder Trim Check: | |
| (1) | Rudder Pedal | Full left |

DO NOT USE FOR FLIGHT

Ground observer reports position of rudder.

- | | | |
|-----|--------------|------------|
| (2) | Rudder Pedal | Full right |
|-----|--------------|------------|
- Ground observer reports position of rudder.
- | | | |
|-----|---|---|
| (3) | Rudder Pedals & Rudder Trim Knob - Centered | Ground observer reports position of rudder. |
| | e. Rudder/Elevator Hydraulic Switches | OFF |
- | | | |
|-----|---------------------------------|---------|
| 11. | Standby Hydraulic Pump Pressure | Checked |
|-----|---------------------------------|---------|
- | | | |
|-----|--|-----------------|
| 12. | Autopilot | Checked and OFF |
| | a. Check turn knob and roll trim knob | |
| | b. Place autopilot master switch ON. | |
| | c. Note trim indicators centered and place servos engage switch to ENGAGE. | |
| | d. Disengage autopilot - the disengage caution light should come on. | |
| | e. Turn autopilot master switch OFF. | |
- | | | |
|-----|--|-----------|
| 13. | Airbrake, Spoiler & Lateral Trim Check | Completed |
|-----|--|-----------|
- This check is made in coordination with ground crew observer. Ground crew observer will report position of spoilers after each movement.
 - Spoiler rigging tolerances are such that the spoiler groups on each wing may not exactly line up during partial or full extension of the spoilers.
- | | | |
|-----|---|--|
| a. | Airbrake & Spoiler Check: | |
| (1) | Move airbrake to position 6. Ground reports: Inboard 60°; outboard 60°. | |

NOTE

- Wing droop associated with high gross weight fuel loads may make it impossible to see the outboard airbrake segments from the cockpit.

(3) Airbrake lever - OFF. Ground reports, "All airbrakes down. "

- | | | |
|-----|------------|---------------------------|
| 14. | Wing Flaps | Checked and up, lever OFF |
|-----|------------|---------------------------|

Flaps should be full down at the time the crew enters the aircraft. Flaps should be checked that they retract in approximately 60 seconds.

- | | | | |
|-----|----------------------|--|---------|
| 15. | Fuel Panel Switches: | Checked | |
| 16. | Gyro Instruments | Checked | |
| 17. | | Oxygen Regulator | OFF and |
| | | 100% OXYGEN (if leaving the aircraft for | |
| | | an extended period of time) | |
| 18. | Bomb Doors | Close | |

Bomb doors will be closed and remain closed on alert aircraft except for required maintenance and special weapons inventory.

STARTING ENGINES AND BEFORE TAXIING**STARTING ENGINES AND BEFORE TAXIING CHECKLIST**

- | | | |
|----|--------------------|-------------------|
| 1. | PARKING BRAKES | SET |
| 2. | BATTERY SWITCH | ON |
| 3. | External Power | ON (if available) |
| 4. | Generator Switches | OFF |
- Momentarily position generator switches to OFF one at a time and check generator circuit breakers open and bus tie circuit breakers closed.
- | | | |
|----|-----------------------|-------|
| 5. | Ground, Close Hatches | Roger |
|----|-----------------------|-------|

WARNING

- The MA-3 external air conditioning unit can build up sufficient cabin pressure to cause the entrance hatch to blow. Ascertain that a sliding window is open prior to opening or closing the hatch.

DO NOT USE FOR FLIGHT

- | | | |
|-----|--|---------------------------|
| 6. | START ENGINES | STARTED |
| 7. | ENGINE ANTI-ICING SWITCH | CLIMATIC |
| 8. | GENERATORS | ON |
| | a. Momentarily hold each generator switch ON to energize the generator field and close the generator circuit breakers (the generators will parallel). | |
| | b. Check that generator and bus tie circuit breaker position indicators show closed and generator ammeter readings are the same. | |
| | c. Using the voltage and frequency selector, check voltage at 205 (± 5) volts and frequency at 400 (± 5) cps on central tie bus, Leave voltage and frequency switch on CENTRAL TIE BUS position. | |
| 9. | Ground, Clear Aircraft for Taxi | Roger |
| 10. | RUDDER/ELEVATOR HYDRAULIC SWITCHES | ON, LIGHTS OUT |
| 11. | Hydraulic System Pressures | Checked |
| 12. | Stabilizer Trim | Checked, takeoff trim set |

NOTE

For thruflight sorties set stabilizer trim for takeoff. No other checks are required.

- | | | |
|-----|--------------------------------------|-------------|
| 13. | Oxygen Regulator | As required |
| 14. | Bomb Doors (Internal Munitions Only) | Closed |

Bomb doors will be closed at this time if internal munitions are aboard. Ground personnel will confirm that bomb doors are clear. Pilot will place the bomb door switch to OPEN to insure that both latches are unlatched, check that the bomb doors not latched light is on, and then place the switch to CLOSED.

NOTE


Whenever bomb bay is empty or during any alert scramble, the bomb doors will be closed while accomplishing the taxiing checklist.

- | | | |
|-----|--|----|
| 15. | ANTICOLLISION & NAVIGATION LIGHTS | ON |
| | Turn lights on immediately prior to taxiing to indicate the aircraft is ready to taxi. | |
| 16. | TAXI ON CREW CHIEF'S SIGNAL | |
| | Pilot announces "Crew stand by to taxi" | |

CAUTION


- Wing flaps must be up. Pilot taxis aircraft straight ahead until ground crew signals that he is clear of the power units. As soon as the aircraft starts rolling, throttles will be retarded to minimum thrust required for taxiing to avoid upsetting the power carts by jet blast. Aircraft must be positioned so that no aircraft will have to taxi over the power carts of another aircraft.

DO NOT USE FOR FLIGHT



DO NOT USE FOR FLIGHT**TAXIING**

The pilot will release his brakes upon receiving "Clear to Taxi" signal from the crew chief. When the aircraft starts to roll, a check of brakes should be made. To steer the aircraft, use rudder pedals. Differential braking is not possible and thrust from the outboard engines is ineffective for turning unless used in conjunction with normal steering. Use the largest radius of turn possible and never attempt to steer when the aircraft is not rolling.

LANDING GEAR PATHS WING TIP PATHS**TURNING RADIUS AND GROUND CLEARANCE****CAUTION**

Use caution when taxiing over wet painted areas because braking conditions may deteriorate to the extent that the braking coefficient is near that for an icy condition.

DO NOT USE FOR FLIGHT**TAXIING CHECKLIST**

1. BRAKES CHECKED
Check wheel brakes for proper operation as soon as possible after aircraft starts to move. Pilots monitor master and central caution lights while taxiing.

CAUTION

- Do not attempt to use crosswind crab when aircraft is not rolling as severe loads would be applied to tires and landing gear.

2. FLAP LEVER DOWN
Pilot lowers flaps after taxiing to insure clearance from ground equipment.
3. BOMB DOORS CLOSED
Pilot places bomb door switch to OPEN to insure that both latches are unlatched, checks that the not latched light is on, and then places the switch to CLOSED position.
5. FLIGHT INSTRUMENTS CHECKED
Check needle for turn indication and ball for freedom of movement; attitude indicator erected and OFF flag out of sight; standby attitude indicator erected and OFF flag out of view; heading indicators for movement in turns; and all pitot-static pressure instruments for correct indications.
6. Generator Panel Checked
Pilot checks ammeters, frequency meter, and voltmeter.
7. Crosswind Crab - Checked
If conditions permit, check operation of the crosswind crab to insure positive response in both directions. Manually turn the crosswind crab knob in each direction, recentering the crosswind crab control with the centering button in each instance. Check both indicator needles for correct indication.


BEFORE LINE-UP CHECKLIST

- | | | |
|----|----------------------|-----------------------------|
| 1. | Parking Brakes | Set |
| 2. | Pitot Heat | ON |
| 3. | YAW SAS SWITCH | ENGAGE |
| 4. | Control Surface Trim | Set |
| 5. | STABILIZER TRIM | CHECKED FOR TAKEOFF SETTING |

NOTE

- During flight, the stabilizer trim switch should be operated in short intermittent bursts to aid in recognizing a malfunctioning electrical trim system before reaching an extreme out-of-trim condition.

- | | | |
|-----|--|-------------------|
| 6. | Airbrake Lever | OFF |
| 7. | WING FLAPS | 100%, LEVEL DOWN |
| 8. | Fuel Panel Switches | Checked |
| 9. | WINDOWS & HATCHES | CLOSED AND LOCKED |
| 10. | Flight Instruments | Rechecked and set |
| a. | The pilot will announce the latest altimeter setting and the known elevation. The pilot will altimeters within 75 feet of the known elevation. | |
| b. | The pilot will announce his HSI and magnetic standby compass indications. The pilot will cross-check the instruments for errors. | |
| d. | Pilot and pilot set attitude indicators to indicate level flight. | |
| 11. | Radio Navigation Instruments | Checked VOR/TACAN |
| 12. | Lights | ON (P/CP) |
- Turn landing, taxi, and crosswind landing lights on for night or day operations unless reflection reduces pilot visibility.

DO NOT USE FOR FLIGHT**TAKEOFF****Illustration of Definitions****TAKEOFF PERFORMANCE****PERFORMANCE DATA**

All takeoff performance data should be determined prior to takeoff. This assures accurate planning and close monitoring of all takeoffs. These data include such items as S1, S2 speeds, takeoff gross weight, runway OAT, field length and altitude, wind direction and velocity, aircraft CG, and the runway gradient. From such items, it may be determined what the takeoff stabilizer settings is, and what the takeoff distance will be. A change in any one of these items will have an effect on takeoff performance.

DO NOT USE FOR FLIGHT**S1 SPEEDS**


DATE: FEBRUARY 1961

DATA BASIS:
ESTIMATED

CONDITIONS:

FLAPS DOWN
8, 7, OR 6 ENGINES

EXAMPLE:

See example problem 1
See example problem 3 for
downwind takeoff data

DO NOT USE FOR FLIGHT**TAKEOFF PLANNING**

Adequate takeoff planning must always include the possibility of poor acceleration during the takeoff run. Although many factors may cause poor acceleration, the most probable cause is engine failure. If such a failure occurs, it must be possible either to stop in the runway distance remaining or to continue the takeoff safely on seven engines at the takeoff throttle setting. The decision whether or not a stop can be made in the remaining runway must be made immediately and with the aid of predetermined criteria. The minimum runway required is the runway length required to accelerate to the decision speed, experience an engine failure, and then take off with seven engines.

TAKEOFF DATA	
Conditions	
GROSS WT <u>360,000</u>	Field P/ALT <u>2000 FT</u>
Rnwy Temp/Dew Pt <u>80°F/40°F</u>	% MAC S ₂ <u>26%</u>
Rnwy Length <u>10,500 FT.</u>	Rnwy Wind <u>30K FROM 40° LEFT</u>
Rnwy Grad <u>0.5% (UPHILL)</u>	Reported RCR <u>23</u>
Information	
Rnwy Available <u>10,300 FT.</u>	Min Rnwy Req <u>6700</u>
Takeoff Dist <u>6000</u>	Stab Trim <u>0.9 N. 4P</u>
Takeoff EPR <u>1.57</u>	X-W Gear Pos <u>4° N.L.</u>
Thrust Gate Setting <u>90°</u>	Grad Correc <u>300 FT.</u>
Decision Dist <u>3000 FT</u>	Min RCR For Takeoff <u>11.6</u>
Distances, Speeds and Times	
S ₁ SPEED <u>103</u> –3 KNOT TOLERANCE = <u>100</u> MIN. IAS	
TIME 70 KNOTS TO S ₁ = <u>11</u> SECONDS	
S ₂	IAS <u>139</u>
CLIMB SPEED – FLAPS DN	IAS <u>180</u>
MIN REC WITH FLAPS UP	IAS <u>180</u>
EMERGENCY BEST FLARE	IAS <u>141.5</u>
EMERGENCY LANDING GROUND RUN	<u>7000</u> FEET

INITIAL TIMING SPEED

Initial timing speed is the speed (70 knots IAS) at which timing is started to determine acceleration characteristics of the aircraft.

TAKEOFF PROCEDURES

Correct takeoff procedures may vary under different takeoff conditions. There are, however, some procedures which are standard for every takeoff.

ALL TAKEOFFS

The stabilizer trim setting will be used for all takeoffs except touch-and-go and taxi back. The wing flaps will be set for 100% down and intermediate settings will never be used.

ROLLING TAKEOFF

In order to minimize the fatigue damage effects to the wing structure, all takeoffs will normally be made from a rolling start. In those situations when safety may be compromised by performing a rolling takeoff or when runway conditions dictate, takeoff may be made from a braked condition. However, maximum thrust operation with brakes locked will be kept to a minimum. When making a rolling takeoff, the aircraft will be aligned with the runway at normal taxi speeds using the radius guide lines.

CAUTION

- Throttles will never be advanced to MRT until within 15° of runway heading.

THROTTLES. The pilot flying the aircraft will advance the throttles deliberately and evenly to MRT. Initial reference to the EPR is not necessary. Full throttle movement should be made in a minimum of 2 seconds and a maximum of 4 seconds. No attempt will be made to steer by throttles as differential thrust is ineffective and reduction of thrust on one side will increase the takeoff ground run.

CAUTION

- MRT is achieved short of full throttle and it is possible to obtain excessive overthrust if throttles are advanced full forward.

STABILIZER TRIM. The stabilizer trim setting required for the takeoff depends on the center of gravity location and aircraft gross weight.

WARNING

- Failure to set the stabilizer correctly could result in:
 1. An accelerated stall if the stabilizer trim is set too nose up.
 2. Longer than predicted takeoff ground runs if the stabilizer trim is set too nose down.

WING FLAPS. The wing flaps are so designed that the highest lift-drag ratio is achieved at the 100% down position. For this reason, they are always used in this position. Because wing flap extension time is 60 seconds and intermediate settings are in-effective, the lowering of flaps during the takeoff roll is not recommended.

CONTROL TECHNIQUE. Steering should be accomplished with the rudder pedals throughout the ground run. The steering system will be effective until sufficient speed is established for rudder control. The takeoff will require a pull force on the control column approximately 5 to 10 knots prior to unstick speed. The control column will be pulled back as required to achieve the computed unstick speed. At the appropriate speed, the forward wheels will come off the runway first and the aircraft will tend to rotate about the rear wheels. Relaxing back pressure at the time the aircraft leaves the ground will stop this pitching action. However, if the stabilizer trim is set too high (aircraft nose up) the control column must be pushed well forward to stop the pitching action. Should rearward control column movement be delayed until just before the takeoff point, the takeoff ground run may be increased as much as 5%.

HEAVY GROSS WEIGHT TAKEOFF

The takeoff and initial portion of the climb out are the critical conditions for an aircraft weighing 450,000 to 488,000 pounds. When takeoff is planned at these weights, performance calculations should be gone over thoroughly not only for normal operation but for emergency conditions as well. After takeoff, there is ample climb performance. Even with one engine out, the aircraft is well above the outboard engine-out minimum control speed.

DO NOT USE FOR FLIGHT**LIGHT GROSS WEIGHT TAKEOFF**

When takeoff is made at light weight, the airspeed and rate of climb increase rapidly after unstick. This condition reduces the time during which trim changes can be made. The pilot should control any nose up rotation with forward control column and nose down trim and check for proper movement of the manual trim wheel. After the landing gear is retracted, the thrust should be adjusted during climb to flap retraction altitude to produce a rate of climb of approximately 1500 to 2000 feet per minute.

Avoid rapid adjustments in thrust level. Anticipate changes sufficiently far in advance to provide time for change in trim.

When partial thrust is used for takeoff, the above problems are minimized and thrust may not have to be adjusted during climb to flap retraction altitude.

OBSTACLE CLEARANCE TAKEOFF

If obstacle clearance is marginal, retrace the landing gear as soon as possible after becoming airborne, leave wing flaps fully extended, and climb at 10 knots above takeoff speed until the obstacle is cleared. Allow the aircraft to accelerate to 180 knots indicated airspeed and continue climb to at least 1000 feet above the terrain before starting flap retraction.

LANDING GEAR RETRACTION. After the aircraft is airborne and brakes have been applied, retract the landing gear. The crosswind crab control knob and indicator will be automatically centered prior to the time the gear retracts.

NIGHT TAKEOFF

When making a night takeoff, use the same procedure as for a day takeoff.

TAKEOFF CHECKLIST**NOTE**

- This checklist will be reviewed prior to takeoff and need not be read during takeoff.

1. Crosswind Crab Set, knob down checked
Pilot sets crosswind crab while taxiing to takeoff position. Pilot checks crosswind crab position indicator for proper setting.
2. Throttles Set
3. Engine Instruments Checked
During initial portion of the takeoff roll, the pilot will check oil pressure (and the low oil pressure warning lights), EPR, rpm, and EGT indicators within limits and will monitor engine instruments during remainder of takeoff roll.
4. Stabilizer Trim Indicator Monitor
Pilot monitors the stabilizer trim indicator during the takeoff roll in order to detect any inadvertent change in takeoff trim setting.
5. 70 Knots Now
At approximately 60 knots. At 70 knots, pilot announces "Now."
6. S1 Now
Pilot announces "Coming up on ___seconds" approximately 3 seconds prior to S1 time. At S1 time, pilot announces "Now". At the same time, the pilot checks his airspeed and announces his decision to takeoff ("Committed") or abort ("ABORT"), based on the time-speed relationship.

WARNING

- Takeoff will not be aborted after S1 unless, in the opinion emergency renders the aircraft definitely unsafe to attain altitude. In those cases where the pilot attempts to abort accept the fact that he will probably fail to stop within the way.

7. Unstick Speed (S2) Now
Pilot calls "Coming up on unstick speed" approximately 5 knots before reaching unstick speed. At unstick speed, pilot announces «Now. "

DO NOT USE FOR FLIGHT**AFTER TAKEOFF****CLIMBOUT PLANNING**

Under some operating conditions, climbout can be the most critical phase of aircraft operation. For this reason, it is essential that the climbout technique be planned during mission planning prior to the flight. The climbout procedures essentially fall into two categories which are explained in the following paragraphs. These are a normal climbout and an obstacle clearance climbout. During mission planning, if it is found that the combination of one engine out, brake release gross weight, runway pressure altitude, OAT, and takeoff thrust is such that less than 300 fpm rate of climb is available, the gross weight must be reduced or a marginal climbout will result.

AFTER TAKEOFF PROCEDURES

After leaving the ground, the wheel brakes will be applied before starting gear retraction to avoid wheel well damage from spinning wheels. The landing gear retraction should be started as soon after unstick as possible. If at a light gross weight when climb is started, the power should be adjusted during climb to flap retraction altitude to a setting which will produce a positive vertical velocity of approximately 1500 to 2000 feet per minute. When partial thrust takeoff procedures are used, the throttles may not have to be adjusted to obtain this desired rate of climb. Keep aircraft trimmed as close as possible to zero stick force in the climb.

STABILIZER TRIM USE AFTER TAKEOFF

The period from takeoff to flaps up requires active stabilizer trim use by the pilot to meet the rapidly changing trim requirements. Stabilizer trim should be utilized as required to maintain stick forces near zero to preclude the rapid development of an out-of-trim condition. Stick forces associated with flaps down are very light even at full travel of the control column and can lead to the false impression that stabilizer trim is not required.

NOTE

Control column force is a function only of control column position and airspeed; this force is not dependent on stabilizer position. If the control column is at full travel and stabilizer trim is being used, no change in control column force will occur until the control column is repositioned by the pilot. A positive method of determining whether or not the trim is working is to note the action of the trim wheel.

Excessive force is not required to position the control column at full travel in the flaps down configuration. Therefore, if a condition develops in which the pilot is holding the control column hard against the stops and not effecting positive control of the aircraft, he must make a conscious effort to utilize stabilizer trim. If this condition has developed and trimming action has been started, the response of the aircraft may not be immediately apparent. Continue trimming until control is regained.



- POINT A. Start takeoff roll with wing flaps down.
- POINT B. Takeoff point; start gear retraction.
- PATH CD. Leave flaps down and climb out at 180 knots IAS to 1000 to 1500 feet above the terrain.
- POINT D. Start flap retraction at 1000 to 1500 feet altitude above the terrain.
- PATH CF. Leave flaps extended and climb at unstick speed plus 10 knots until the obstacle is cleared.
- POINT F. Maximum desired altitude for clearing obstacle (at least 1000 feet above terrain).
- PATH FG. Start flap retraction at 180 knots IAS; maintain sufficient rate of climb.

DO NOT USE FOR FLIGHT

POINTS E Points at which flaps are up. Accelerate to the best
AND G. Climb speed

NORMAL CLIMBOUT PROCEDURE


After unstick, the aircraft is accelerated to 180 knots IAS and a flaps down climbout made to at least 1000 feet above the terrain. At this point, flap retraction will be initiated. The aircraft will be accelerated on takeoff heading during flap retraction whenever possible. The airspeed must be maintained above the minimum recommended with flaps up.

OBSTACLE CLEARANCE CLIMBOUT PROCEDURE

When obstacles near the field must be cleared on takeoff, the climbout performance becomes very important. A high angle of climb for clearing close obstacles is maintained by leaving the flaps down and climbing at 10 knots above unstick speed until obstacle is cleared.

FLAP RETRACTION PRECAUTIONS

During flap retraction, the speed schedule should be maintained within ± 10 knots.



This schedule gives a safe margin between flap placard and minimum speeds. If the airspeed is low, the vertical velocity should be reduced or power added. During the flap retraction cycle, it is required that the pilot monitor the aircraft attitude as closely as possible, keeping the aircraft trimmed to a zero stick force, especially during the last 20' of flap retraction. If the climbout has been properly planned and no emergency develops, a satisfactory vertical velocity can be maintained while accelerating during flap retraction. However, under conditions of high gross weight, high OAT, and high field elevation, or any combination of these factors, it may be impossible to maintain a positive vertical velocity during the latter part of the flap retraction period. Flaps should not be retracted in a turn, and the speed schedule of 180 knots IAS at 100% flaps down, 200 knots IAS - flaps 50%, 210 knots IAS - flaps 30', and 230 knots IAS - flaps full up should be followed. In any event, maintain a sufficient positive vertical velocity to keep from exceeding the flap placard speed of 225 knots IAS at the 50% position and 253 knots IAS at the 10% position.

WARNING

- The OFF flag will not appear during every attitude indication failure. Therefore, it is possible that malfunction of the attitude indicator portion of the attitude-director indicator might be determined only by crosschecking it with the turn and slip indicator and the other remaining flight instruments.

SUMMARY OF AFTER TAKEOFF PROCEDURES

Climb out with flaps full down at 180 knots IAS to an altitude of at least 1000 feet above the terrain and retract the flaps. If a positive vertical velocity of 1000 fpm is not attained when reaching 1000 feet above the terrain, flap retraction will be delayed until an altitude of 1500 feet above the terrain is reached. If an obstacle must be cleared, climb out with flaps down at unstick speed plus 10 knots until a safe altitude has been reached.

DO NOT USE FOR FLIGHT**AFTER TAKEOFF - CLIMB CHECKLIST**

- | | | |
|----|--------------------|-----------------|
| 1. | Landing Gear Lever | GEAR UP, six up |
|----|--------------------|-----------------|

CAUTION

If any gear fails to indicate up and locked, to prevent system damage, do not recycle the landing gear system prior to initiating emergency procedure.

- | | | |
|----|------------|----|
| 2. | Flap Lever | UP |
|----|------------|----|

At 180 knots IAS and a minimum altitude of 1000 feet above the terrain, the pilot directs the pilot to raise the flaps. If a positive vertical velocity of 1000 fpm is not attained when reaching 1000 feet above the terrain, flap retraction will be delayed until an altitude of 1500 feet above the terrain is reached. At the appropriate time, the pilot advises, "Flaps coming up, flaps 50%, flaps 30%, and flaps full up. " In addition, the pilot monitors the flight instruments, including the airspeed, during flap retraction. As a guide, the normal speed schedule during flap retraction should be approximately 180 knots IAS at 100%, 200 knots IAS at 50%, 210 knots IAS at 30%, and 230 knots IAS when flaps reach the full up position. If the actual indicated airspeed varies from these values by 10 knots or more, the pilot should so advise the pilot so he can make necessary pitch changes.

- | | | |
|----|------------|-----------|
| 3. | Throttles | Set |
| 4. | Fuel Panel | Checked |
| 5. | Altimeter | Set 29.92 |
- Pilot and pilot will periodically cross-check altimeter readings in flight.

CLIMB

NRT will normally be used for climb. If climbs are made at less than normal rated thrust, a loss of range will result because of the excessive time spent in climbing. MRT may be used for emergency conditions or as mission requirements dictate. A point on the cruise flight path will be reached at approximately the same time regardless of whether military rated thrust or normal rated thrust is used for the climb. Less fuel will be required when military rated thrust is used, but engine life probably will be shortened slightly since higher engine speeds and higher temperatures will be encountered.

CRUISE

With the engines stabilized at cruise flight condition, the pilot should monitor the oil temperature of each engine at convenient intervals and observe any significant temperature variations between engines.

RANGE

Normally, a combat mission will be flown using procedures which will produce maximum range. The performance of a jet aircraft is such that maximum range is attained by flying at one particular Mach number and gradually increasing altitude as aircraft weight is decreased through fuel consumption. The rate of climb required is very small (averaging from 16 to 20 feet per minute or about 1000 to 1200 feet per hour). Therefore, rather than attempt to fly at some specified rate of climb, check the flight altitude with that given in the altitude curve at frequent intervals (not to exceed 30 minutes) to assure that the proper climbing flight path is being maintained. The autopilot altitude hold position may be used until the airspeed increases, at which time a shallow climb should be initiated to place the aircraft at the correct altitude for the decreased weight. This step climb procedure will be repeated as necessary. The cruise True Mach number should be checked frequently by means of the airspeed indicator. The machmeter may be inaccurate, causing a range loss of several percent. There is only one weight-altitude schedule which will result in maximum range. Best range (constant altitude) cruise is usually used for a noncombat mission because the difference in range between this type of cruise and maximum cruise is not great if the altitude is above 35,000 feet.

DO NOT USE FOR FLIGHT**LOW ALTITUDE TACTIC**

Penetration airspeed to the low altitude entry point will normally be 280 K2AS, unless aircraft restrictions apply or using commands direct otherwise.

OPERATION

Present low altitude operational information is based upon the results of low altitude flight tests. During these tests, the aircraft and its systems were operated at near maximum design capability. With the requirement of all-weather flying at airspeeds up to the design limit of the aircraft, adequate preflight planning is especially essential to successful completion of a low altitude mission. Icing conditions at low altitudes and high speeds can be more severe than those normally encountered. Also, it is extremely difficult to anticipate icing conditions during low altitude operation, particularly at night. Crew coordination is considered critical when flying at low altitude. There have been some unusual psychological effects on crew members and fatigue is found to increase much more rapidly at low altitude than at high. There is considerable difficulty for pilots in interpreting readings of certain instruments while bouncing due to turbulence; however, it is fairly easy to determine the range of scale which the instrument needle is in, and generally, this is sufficient. Adverse effects which are frequently encountered at low altitude and which must be considered when planning a mission are increased turbulence, reduced vision, reduced radar range, the inconsistency of winds due to terrain effect, and extreme difficulty in the use of celestial navigation because of turbulence and the frequency of overcasts.

LOW LEVEL DESCENT CHECKLIST**NOTE**

- The pilot should be alert for the condition of forward throttle creep from IDLE position throughout descent to preclude unscheduled power resulting from advanced throttle settings.

- | | | |
|---|--------------------------------------|---------------|
| 1. | Altimeter Settings | Obtained |
| Obtain updated forecast altimeter settings values from a designated station. | | |
| 2. | EVS Power Switches | ON |
| 3. | Terrain Display Mode Selector Switch | AS REQUIRED |
| 4. | Anti-Icing Panel | Climatic |
| 5. | Taxi Lights | ON |
| On training missions turn taxi lights on during night or day operations unless reflection reduces pilot visibility. | | |
| 6. | Altimeters | Set |
| Set altimeters to station pressure immediately prior to initiating penetration or upon passing through transition altitude. | | |
| 7. | Autopilot | Disengaged |
| 8. | Radar & Pressure Altimeters | Cross-checked |

CLIMB AFTER LOW LEVEL CHECKLIST

After completion of low level tactic when climbing back to altitude, perform the items in the "Climb After Low Level" checklist.

NOTE

- This check will be accomplished prior to descent to low level.
- This check will be accomplished after a 1-minute warmup period of the terrain computer.

- | | | |
|----|--------------------------------------|-----------|
| 1. | Throttles | Set |
| 2. | Terrain Display Mode Selector Switch | OFF |
| 3. | Altimeter | Set 29.92 |
| 4. | Level-Off Check | Completed |
| 5. | Taxi Lights | OFF |

DO NOT USE FOR FLIGHT**DESCENT**

The following procedures are for all letdowns where there is no range emergency and should be accomplished as follows:

WARNING

- Care should be taken to retrim between each 2-unit increment of airbrake operation.

NORMAL DESCENT

- Maintain cruising altitude until reaching the computed distance from the landing base. This distance will depend upon aircraft altitude and weight at the end of mission.
- Lower the landing gear and retard all throttles to the IDLE stops. Observe the gear extension limits.
- Extend airbrakes to position 4 or as required.
- Make descent at 240 KIAS or Mach .75, whichever is slower.

NOTE

- Rate of descent may be varied (by airbrake position) but does not exceed 6000 fpm.

ENROUTE DESCENT

- Throttles idle, gear up, and airbrake as necessary to provide desired airspeed and rate of descent to comply with ATC requirements for the particular enroute descent.
- The many variables of an enroute descent will prevent precise calculations of range-time-fuel performance.

TACTICAL DESCENT

Assuming the descent will start from cruise altitude and airspeed, the initial task is to retard the throttles to idle and establish a nosedown attitude of approximately 10°. Extend airbrakes to position 6 in increments of 2, trimming to approximate zero stick force prior to raising the airbrakes to the next position. Maintain approximately zero stick force by continually trimming the aircraft during descent. Maintain approximately 10° nosedown attitude and a speed schedule of .84 Mach until reaching 305 KIAS. Maintain 305 KIAS during the remainder of the descent. Close coordination between the pilot and pilot is required to insure that a transition is made from indicated mach to indicated airspeed. Pilot will coordinate with the navigator as to level-off altitude to be used for this maneuver. Initiate level off approximately 1000 feet above the desired level flight altitude by retracting airbrakes from position 6, to position 4, to position 2, and retrimming. Complete airbrake retraction at approximately 500 feet above the desired level flight altitude, retrim, and add power as required.

NOTE

- If turbulence is encountered such that the airspeed indicators are hard to read, hold a 10° nosedown attitude until the turbulence has been penetrated. Aircraft attitude should not exceed 12° nosedown.

DESCENT AND LANDING CHECKLIST

- | | | |
|----|------------------------|----------|
| 1. | EVS | ON |
| 2. | Penetration & Approach | Reviewed |

Obtain approach, landing weather, compare forecast versus reported altimeter setting, and review the planned penetration and approach. This review will include navigation aid frequencies, minimum and emergency safe altitudes, descent rates, minimums for the approach to be flown, missed approach procedures, and aerodrome sketch. As a minimum the pilot flying the approach will brief the crew on the descent rate, MDA/DH/VDP and missed approach procedures for the planned approach. Lost communications procedures will be coordinated if required. During the descent and approach other crewmembers will back up the pilot flying and report any deviation from prescribed procedures.

DO NOT USE FOR FLIGHT

Active Runway _____ Wind _____ Temp _____
 PA _____ RCR _____ Ceiling & Vis _____
 RVR _____ Altimeter _____
 Forecast Altimeter _____ Dest _____
 Alt _____

- | | | |
|----|------------------------|----------------------|
| 3. | Landing Data | Computed and checked |
| 4. | Nav Mode Select Switch | VOR/TACAN |
| 5. | Fuel Panel | Checked |
| 6. | Anti-Icing Switches | Climatic |
| 7. | Lights | ON |
- Turn landing, taxi, and crosswind landing lights on for night or day operations unless reflection reduces pilot visibility.

- | | | |
|----|-----------|------------|
| 8. | Autopilot | Disengaged |
|----|-----------|------------|
- Autopilot will be disengaged for penetration.
- | | | |
|----|-----------|-----|
| 9. | Altimeter | Set |
|----|-----------|-----|
- Reset altimeters to station pressure immediately prior to initiating penetration or upon passing through transition altitude.

- | | | |
|-----|--------------|------------------------------|
| 10. | Landing Gear | DOWN (if required), six down |
|-----|--------------|------------------------------|
- The landing gear may be lowered at the pilot's discretion during an enroute descent or a published penetration depending upon the rate of descent required. Pilot moves landing gear lever to GEAR DOWN and checks for positive engagement of the pawl in the gear down detent by forcibly and positively pushing in on the landing gear handle after the handle is in GEAR DOWN. Pilot checks operation of the landing gear warning light. Both pilots check that the warning light is out, and that all six gears indicate down and locked.

CAUTION

- To prevent system damage, if any gear fails to indicate down and locked, do not recycle the landing gear system prior to initiating emergency procedure.

- | | | |
|-----|-----------|-----|
| 11. | Throttles | Set |
|-----|-----------|-----|

NOTE

- The pilot should be alert for the condition of forward throttle creep from IDLE position throughout descent to preclude unscheduled power resulting from advanced throttle settings.
- To reduce engine compressor stalls, anti-icing should be turned off when making an engine deceleration above 15, 000 feet. Anti-icing can then be turned on after the engines have stabilized at the reduced throttle settings.

- | | | |
|-----|-----------|-----|
| 12. | Airbrakes | Set |
|-----|-----------|-----|
- The airbrake lever will normally be set at position 4; however, airbrakes may be used as required.

- | | | |
|-----|------------|------|
| 13. | Wing Flaps | 100% |
|-----|------------|------|
- Allow aircraft to decelerate to 220 knots IAS. Pilot extends flaps at the request of the pilot and monitors flap indicator to ascertain both flaps are extending simultaneously. Pilot reports when the flaps are 50% and full down. Flap lever will be left in DN position. Flap extension time is 60 seconds. Flaps may be extended during the penetration descent as required.

- | | | |
|-----|---------------------|---------|
| 14. | Fuel Panel Switches | Checked |
|-----|---------------------|---------|

- | | | |
|-----|------------------|-----------|
| 15. | Best Flare Speed | Rechecked |
|-----|------------------|-----------|
- Best flare speed for airbrake position 4 is approximately 15 knots above the minimum touchdown speed. Minimum touchdown speed is the same value as unstick speed and provides a 7 to 12 knot margin above initial stall buffet speed.

- | | | |
|-----|--------------|----------------|
| 16. | Landing Gear | Down, six down |
|-----|--------------|----------------|

- | | | |
|-----|----------------|--------------|
| 17. | Crosswind Crab | Set, checked |
|-----|----------------|--------------|
- Obtain wind direction and velocity. Compute and set crosswind crab as required. If crosswind crab is not to be used, knob and position indicator must be checked for zero setting and gear position. Pilot checks crosswind crab position indicator for the proper setting.

DO NOT USE FOR FLIGHT

18. Target Trim

Noted

When aircraft is established on final approach in landing configuration (landing gear and flaps down and airbrakes in planned position) at best flare speed plus 10 KIAS, pilot not flying the aircraft will note the stabilizer trim setting for zero stick force. He will call out this value as target trim during an approach with airbrakes in position 0 or 2. For an approach with airbrakes in position 4 or 6, he will compute a trim value two units in the noseup direction from that noted and call out this computed value as target trim.

NOTE

- It is preferable to note stabilizer trim while in straight and level flight. In VFR traffic patterns or situations where it is not readily feasible to establish straight and level on final approach, the stabilizer trim target setting during descent may be used provided rate of descent does not exceed 1000 feet per minute.

19. Landing Check

Completed

- a. Gear
- b. Flaps
- c. Airbrakes 4 or as required
- d. Lights

A check of the above items will be made when on final.

BEFORE LANDING


The before landing procedures are given in the "Descent and landing" checklist.


APPROACH

Since conditions at airports are continually changing, the landing approach techniques must be varied to meet existing conditions. In general, a normal landing pattern can be used. With full airbrakes, the gliding angle is approximately the same as that for a propeller-driven aircraft.

DO NOT USE FOR FLIGHT

APPROACH PROCEDURE (VISUAL PATTERN)



DO NOT USE FOR FLIGHT

Referring to the figure, the downwind leg is entered at the altitude specified in applicable regulations. The "Descent and Landing Checklist" will be completed at this point and the airspeed reduced to 30 knots above computed best flare speed. The turn from the downwind leg will be a descending 90° turn to the base leg with a reduction in airspeed and altitude. Roll out to a wings-level attitude while descending on the base leg for sufficient duration (approximately 10 seconds) to allow for visual clearance of other aircraft in all directions. Maintain 20 knots above computed best flare speed until starting turn to final approach. A 90° descending turn to final approach will then be initiated and, at the completion of rollout on final approach, the airspeed will be 10 knots above computed best flare speed, minimum altitude as specified in applicable directives. A 30° bank will be the maximum allowable in the traffic pattern. The 10 knots above best flare speed will be maintained until the flare point is reached. As the flare point is reached and the aircraft is

DO NOT USE FOR FLIGHT

rotated for landing, the throttles will be retarded so as to cross the end of the landing runway at best flare speed. After touchdown, the airbrakes should be fully extended and the drag chute deployed.

NOTE

- The pilot should be alert for the condition of forward throttle creep from IDLE position throughout approach and landing to preclude unscheduled power resulting from advanced throttle settings.
- If a crosswind leg is flown, the aircraft will be rolled out to a wings-level attitude on the crosswind leg for sufficient duration to permit visual clearance of other aircraft in all directions.
- The pilot's and/or pilot's sliding window may be opened at normal traffic pattern speeds and maneuvers provided all hatches are in place. If a hatch has been released, the opening of a sliding window should be avoided as inward acting airloads may cause the window to blow into the cabin area.

LANDING**LANDING WITH GUSTY WIND CONDITIONS**

It is not necessary to increase the final approach speed for gust velocities up to and including 15 knots. For gust velocities in excess of 15 knots, the final approach speed should be increased two-thirds of the gust velocity in excess of 15 knots. For example, with a wind velocity of 20 knots with gusts to 50 knots, 10 knots would be added to the final approach speed (total gust velocity 30 knots; $30 - 15 = 15$ knots; $15 \times 2/3 = 10$ knots).

TOUCHDOWN


The recommended touchdown is with the rear gear first at minimum touchdown speed. Refer to Part 8 of the Appendix for landing speeds. This allows for an adequate flare without a bounce. However, if the forward gear is too high when the rear gear touches, a hard landing may result. Full airbrakes should be applied immediately after touchdown provided there is no bounce. With the antiskid system operative, the wheel brakes may also be applied immediately after touchdown although this decreases brake service life. The runway available will determine when the wheel brakes should be applied.

NOTE

- The front gear is well forward of the CG and if allowed to touch down first, a bounce is almost certain to occur. This usually is the result, of too much speed.

NOTE

- Sustained runway wind velocity plus one-third of the gust factor will be used to compute crosswind crab settings when landing with gusty wind conditions.
- If a crosswind cannot be compensated for by use of the crosswind crab system, a landing is not recommended.
- If the wind is a variable wind, the average heading of this variable wind should be used.
- Prior to or during the time the aircraft is in the traffic pattern, a decision must be made as to whether or not the crosswind crab system is to be used. After obtaining the wind direction and velocity from the tower located at the field at which the landing is to be made, compute the crab angle for the wind and landing gross weight.

DO NOT USE FOR FLIGHT**CROSSWIND LANDING****WITH USE OF CROSSWIND CRAB SYSTEM**

Smooth landings can be made through use of the crosswind crab system even though crosswinds of high velocity are encountered. Such landings also require additional effort from the pilot. Touching down the aircraft in a crabbed attitude may seem strange the first few times such landings are tried, but this technique is easily learned by the pilot.

CROSSWIND CRAB SETTING. After voice radio contact has been established with the tower, obtain the runway surface wind and direction. The most accurate wind measurements are obtained close to the ground. Limited experience indicates that 50% of tower values closely approximate runway winds. If only uncorrected tower wind values are used, it is recommended that the crab setting be established using 50% of tower values. From this data, determine the crosswind crab setting to be used in landing. After the landing gear has been extended, turn the crosswind crab control knob until the miniature aircraft and pointer on the indicator point to the crab angle setting determined for the wind and gross weight. Extend the flaps, raise airbrakes to position 4, and control the airspeed in the same manner as for a normal approach. After rolling out onto final approach and after the aircraft is crabbed into the wind to establish a flight path straight down the runway, recheck the position of the miniature aircraft and pointer on the crosswind crab control indicator. The nose of the aircraft, as well as the nose of the miniature aircraft and pointer on the indicator, should always be pointed off the runway into the direction of the wind component.

CAUTION

- If rudder trim is used on landing, be certain that the crosswind crab control knob is not turned instead of the rudder trim knob since they are located concentrically.

LANDING ROLL. After the aircraft is on the runway, more and more lateral control will be required to hold the wings level as the speed decreases. If difficulty is encountered in maintaining track down the runway at low speeds, the control wheel should be centered since an asymmetric spoiler condition will cause an unfavorable turning force. The crosswind crab system is not used to steer the aircraft on the ground.

NOTE

- When landing under conditions of high crosswinds, light gross weights, and a slippery runway, loss of steering may result.

DO NOT USE FOR FLIGHT

- Be alert for indication of a missetting of crosswind crab at touchdown. Corrections should be accomplished by normal rudder pedal steering. Do not use the crosswind crab control knob for steering. On very smooth landings, a missetting of the crosswind crab will not immediately manifest itself by the aircraft diverging off either side of the runway; the first indication of incorrect setting will be a deceleration force due to tires scuffing.

WITHOUT USE OF CROSSWIND CRAB SYSTEM

If the crosswind crab system is not to be used because of a malfunction, the landing may be made by approaching fully crabbed with rudder and lateral controls centered. If desired, a combination of crabbing into the wind and a slight lowering of the upwind wing may be accomplished, but the wing should not be lowered to such an extent that the tip gear touches the ground first upon landing. Touchdown in the crabbed attitude with normal landing rates of descent will not induce detrimentally high side loads on the landing gear since the gear is lightly loaded at this time. By landing rear gear first, the aircraft will tend to pivot about the rear gear and thereby reduce the crab angle by the time the forward gear touches. Full airbrakes should be applied and the drag chute may be deployed at touchdown since forward gear steering will be adequate by the time the drag chute becomes effective.

MINIMUM RUN LANDING

The approach for a minimum run landing should be planned so as to arrive over the end of the runway with the throttles at IDLE and at a speed as close to best flare speed as possible. A minimum run landing is accomplished by having the brake antiskid system operative, deploying the drag chute, using full airbrakes after touchdown, applying wheel brakes immediately after touchdown, and continuing to apply brakes throughout the landing roll. The drag chute provides considerable deceleration force over the first portion of the landing roll while the wheel brakes have a small decelerating effect because the wheels are lightly loaded. As the aircraft decelerates, the drag chute becomes less effective while the brakes become more effective.

CAUTION

- All landings should be planned from a landing distance standpoint as though the drag chute were not installed. The chute should be considered only an aid to braking and a means of reducing tire and brake wear.

WHEEL BRAKE APPLICATION

Each wheel is equipped with a complete brake antiskid assembly, eight units per aircraft. Therefore, when one wheel approaches a skid and the brake pressure is released by the skid detector, no other wheel brake assembly is affected. Regardless of this desired feature, however, the wings should be held as near level as possible during the landing roll so that all wheels are on the ground. If the wings are not level, the high tire on each landing gear becomes lightly loaded causing a loss in braking effectiveness because of the limited braking torque on the heavily loaded wheels. Maximum braking effectiveness with antiskid operative is obtained by depressing the rudder pedals fairly hard and letting the individual brakes cycle as required to prevent skids. Application of a fairly hard force on the brake pedals will result in the heavily loaded wheels being cycled at a slower and more desirable rate, while the lightly loaded wheels are cycled quite rapidly. This cycling can be felt by the pilot and becomes quite noticeable, especially if several of the gears cycle on and off at approximately the same time. If several of the gears do start to cycle in unison and cause a violent vibration, the pedals should be released momentarily and then reapplied. The difference between conventional braking and use of antiskid is that with antiskid operating, the brakes can be applied earlier in the landing roll and maximum braking can be maintained throughout the entire roll without excessive tire wear due to skids. On slippery surfaces at low taxi speeds, wheel deceleration is very fast when brakes are applied and skid signals are generated more frequently, releasing brake pressure before a locked wheel occurs. Aircraft deceleration is not felt by the pilots because of the fast cycling of the antiskid system. However, the use of antiskid under these conditions is the recommended procedure since attempting to brake without it results in greater stopping distances.

DRAG CHUTE DEPLOYMENT

Normally, the drag chute will be deployed on all landings. The drag chute should be deployed only after touchdown. The time required for the drag chute to open is about 2 seconds after the drag chute lever is pulled to DEPLOY position. It is not recommended that the drag chute be deployed during the flare while the aircraft is floating since there is a tendency for the aircraft to pitch up or down, depending on the speed, and to drop in due to rapid deceleration. See Section V for drag chute limitations.

DO NOT USE FOR FLIGHT**CAUTION**

- Dragging the chute along the runway causes considerable wear on the chute suspension lines and canopy. If possible, keep engine maintain higher approach speed to the flare thrust high enough at the lower ground run speeds to hold the chute off the ground until the aircraft can be turned off the runway. Request the ground crew to stand by to retrieve the chute as soon as the aircraft is clear of the runway and the chute is jettisoned.
- During prevailing surface winds of 15 knots or greater, do not turn more than 90° away from the wind while drag chute is deployed.

NIGHT LANDING

The procedures and techniques used for a night landing are the same as those used for a normal day landing. In addition, the terrain clearance light may be used at the pilot's discretion.

OBSTACLE CLEARANCE LANDING

If a relatively high altitude must be maintained to clear some obstacle located within the traffic pattern, a steeper approach must be made after clearing the obstacle. A normal approach with full flaps and airbrake lever in position 4 is made with sufficient altitude to clear the obstacle. If a steeper approach is desired, airbrakes position 6 may be used. Should the obstacle be located close to the end of the runway, it may be necessary to place the airbrake lever in position 6 and steepen the approach before passing over the obstacle. In this case, the pilot should approach at a sufficiently high altitude to assure clearance with the steeper approach. If full airbrakes are used, the rate of descent will be higher than normal and the flare will have to be started earlier.

NOTE

- If touchdown is to be made with full airbrakes, maintain higher approach speed to the flare point.

LANDING CHECKLIST

Accomplish after touchdown (need not be read).

- | | | |
|---|-----------------------------|------------|
| 1. | Airbrake Lever | Position 6 |
| 2. | Drag Chute Lever | DEPLOY |
| Drag chute will be deployed on pilot's command. In the event a go-around is not anticipated and the drag chute does not deploy, do not jettison the drag chute. | | |
| 3. | Wheel Brakes | Checked |
| After establishing a stable ground roll, brakes will be checked for operation followed by intermittent application of brakes as required. | | |
| 4. | Hydraulic System | Checked |
| Check all hydraulic pumpout lights off. | | |
| 5. | Crosswind Crab Control Knob | Centered |

GO-AROUND

The decision to make a go-around should be made as early as possible since engine acceleration time is a factor and approach speeds are relatively close to touchdown speeds. Normally, this decision can be made prior to touchdown. As soon as it has been decided to go-around, advance throttles to "go-around thrust" which is the thrust required to arrest descent and produce a satisfactory rate of climb and/or acceleration, retract airbrakes, trim as required, and, after it is certain that the aircraft will not touch the ground, retract the landing gear. Further thrust refinements will be accomplished as necessary to obtain the desired performance during the go-around.

WARNING

- In cases where a go-around is initiated just prior to or during the landing flare and where adequate runway is remaining, it may be necessary to maintain a touchdown attitude, contact the runway, then retrim the aircraft during the ground run before initiating power application for a go-around.
- The thrust produced by the turbofan engines demands the use of proper procedure and pilot technique when executing touch-and-go or go-around maneuvers. If MRT is applied for touch and go or go-around below approximately 340, 000 pounds, the aircraft will respond very rapidly. Immediate nose down trim will be required as a result of 1) any increase in airspeed, 2) the aft cg shift due to fuel movement to the rear of the tanks in the case of partially full tanks, and 3) the nose up tendency produced by the engine thrust line being below the cg. The adverse effect on aircraft trim is much more pronounced at light gross weights. At light gross weights, nose down trim must be applied simultaneously with any large increase in thrust to maintain positive control of the aircraft. Conversely, any large decrease in thrust may be critical. If the aircraft has been allowed to rotate to an extreme nose high attitude and is no longer accelerating at MRT, any attempt to control the pitch by thrust reduction at this time will result in a stall. If the pitch attitude has progressed to this point, the last resort for possible recovery is to maintain MRT for the pushover and start retrimming as the airspeed begins to increase. It must be noted that MRT is achieved short of full throttle and it is possible to obtain excessive overthrust if throttles are advanced full forward.
- The decision to go-around or land on the remaining runway must remain with the pilot based upon all factors involved. However, if a situation is allowed to develop, which in the pilot's judgement, requires a go-around from a low airspeed/low altitude condition, the pilot must be extremely aware of the hazards of aircraft pitch up and the items affecting pitch control. An unscheduled go-around with a mistrim condition can occur where several other trim items occur simultaneously due to fuel shift, thrust, airbrakes, and ground effect. Each item can be controlled by the use of elevator alone. But when several of these items are combined the elevator, which is the primary flight control system, may not have sufficient authority, and additional authority must be obtained from the stabilizer or airbrakes. A 20 degree pitch attitude and strong buffet can easily occur in 3 seconds from which a recovery may not be possible.

For pilot comfort and ease of flying, the thrust should be adjusted during climb to flap retraction altitude to a setting which will produce a rate of climb not to exceed approximately 1000 feet per minute. If thrust has been reduced during this initial climb, it may be necessary to add power during flap retraction to maintain the desired speed schedule and to preclude loss of altitude. When the aircraft reaches 1000 feet and 180 knots IAS, the flaps may be retracted. However, if a positive vertical velocity of 1000 feet per minute is not attained when reaching 1000 feet above the terrain, flap retraction will be delayed until an altitude of 1500 feet above the terrain is reached. During the flap retraction cycle, it is required that the pilot monitor his aircraft attitude as closely as possible, keeping the aircraft trimmed to a zero stick force especially during the last 20%.

WARNING

- A go-around should not be attempted if the drag chute has been deployed since it is possible that the drag chute may not jettison. Sufficient thrust is available from eight engines to fly the aircraft with the drag chute deployed at weights below approximately 300, 000 pounds; however, this is not recommended since the associated control problems have not been flight tested.

NOTE

- When go-around is accomplished during closed traffic pattern work, the pilot may, at his discretion, leave the landing gear and flaps down.

DO NOT USE FOR FLIGHT**NOTE**

- If a go-around is required under low altitude/low airspeed conditions pilots may not have sufficient time to refer to the checklist. Therefore this checklist should be accomplished as necessary and need not be read. When a safe altitude and airspeed is attained the pilots will review the checklist and complete required items.

GO-AROUND CHECKLIST

1. Go-Around Thrust

Set

The pilot will advance the throttles as required to arrest descent and produce a satisfactory rate of climb and/or acceleration. Further thrust refinement will be accomplished as necessary to obtain desired performance during the go-around. The throttle position should not exceed the thrust gate initially. The pilot monitors the engine instruments and notifies the pilot of any abnormal engine operating characteristics.

WARNING

- If the throttles are advanced beyond the thrust gate position for any reason, extreme care should be exercised due to nose up rotation during acceleration.
- If a go-around is initiated after starting landing flare, immediately counter the resultant pitching moment with nose down elevator. Throttles will not be advanced beyond the thrust gate position without simultaneously resetting the stabilizer toward target trim. Failure to retrim during the thrust application phase of a go-around can result in pitch-up, which combined with other pitch trim items, will exceed nose-down elevator authority. Also, with asymmetrical thrust, power must not be applied faster than any generated roll-yaw problem can be controlled.

2. Airbrake Lever

OFF

Pilot retracts airbrakes, levels off, and checks for a positive increase of airspeed.

3. Trim

As required

At all times during go-around, pilot makes a conscious effort to keep the aircraft trimmed to zero stick force.

4. Landing Gear Lever

As required

Pilot retracts the gear when it is established that aircraft will not contact the runway.

5. Thrust

Adjusted

Pilot accelerates to desired IAS (best flare speed plus 30 KIAS or 180 KIAS) and adjusts thrust to establish a rate of climb of approximately 1000 fpm.

6. Wing Flaps

As required

Flaps will be retracted in a wings level attitude, using the normal speed schedule and in accordance with the flap retraction procedures outlined in the "After Takeoff-Climb Checklist," this section. If the flaps are raised to accomplish flaps up training, or if the pilots' intentions are to remain in the aircraft traffic area/terminal control area, accelerate to approach speed plus 30 KIAS.

NOTE

- Accomplish "After Takeoff - Climb" or Traffic Pattern" checklist, as applicable.

TOUCH-AND-GO LANDING

Failure to lower airbrakes and retrim the aircraft to target will result in excessive nose up rotation immediately following unstick. The large amount of thrust available from the turbofan engines makes the use of partial thrust procedures for touch and go of the utmost importance to preclude a possible hazard due to the rapid acceleration. The thrust gate is used to provide a satisfactory partial thrust level for touch-and-go landings. Rapid pitch changes must be countered immediately by continuous use of stabilizer trim in addition to control column movement. Touch-and-go landings can normally be performed within the limits shown in the amplified "Touch-and-Go Landing" checklist unless additionally restricted by the major command concerned.

DO NOT USE FOR FLIGHT**TOUCH-AND-GO LANDING CHECKLIST****NOTE**

- This checklist will be reviewed prior to touch-and-go landings and need not be read while on the runway.

- | | | |
|----|-----------------|------------|
| 1. | Airbrake Lever | Position 6 |
| 2. | Stabilizer Trim | Reset |

WARNING

- If the stabilizer trim is not reset prior to takeoff, the excessive amount of nose up trim will cause a nose up rotation after takeoff. Any pitch attitude changes following a takeoff will be countered immediately by continuous use of the stabilizer trim in addition to control column movement.

NOTE

- The operation of the stabilizer trim mechanism during the ground roll of touch-and-go landings is considered to be an inflight procedure and inflight operation limitations will apply.

- | | | |
|----|----------------|-----|
| 3. | Airbrake Lever | OFF |
|----|----------------|-----|

It is essential that the airbrake lever be returned to OFF before executing the takeoff following a touch-and-go to preclude an unexpected pitchup following takeoff.

- | | | |
|----|-----------|---------|
| 4. | Throttles | Advance |
|----|-----------|---------|

The pilot performing the takeoff after a touch-and-go landing will advance the throttles slowly to an intermediate setting allowing engines to accelerate and stabilize prior to advancing the throttles to the thrust gate. Do not advance throttles until the trim has been reset. The pilot will monitor the engine instruments. Further thrust refinement will be accomplished as necessary to obtain the desired performance during takeoff and climb. See "Go-Around," this section, for thrust effects. Premature liftoff prior to unstick speed (minimum touchdown speed) can be hazardous since there is only a 7 to 12 knot margin between unstick speed and initial stall speed. Premature liftoff can only occur when stabilizer is mistrimmed and/or excessive back column is introduced prior to unstick. Accelerate to best flare speed plus 30 KIAS on climbout.

NOTE

- Accomplish "After Takeoff - Climb" or "Traffic Pattern" checklist, as applicable.

TRAFFIC PATTERN CHECKLIST

- | | | |
|----|----------------|------------|
| 1. | Airbrake Lever | As desired |
|----|----------------|------------|
- Airbrakes may be used as desired until on final approach when they will normally be Position 4.

- | | | |
|----|------------------|--------------------------|
| 2. | Planned Approach | Reviewed (if applicable) |
|----|------------------|--------------------------|
- Check the appropriate navigation aids tuned. Altitude restrictions, descent rate, MDA/DH/VDP, and missed approach procedures will be emphasized. Review if type approach/pilot changes.

- | | | |
|----|------------------|---------|
| 4. | Wing Flaps | 100% |
| 6. | Best Flare Speed | Checked |
| 7. | Thrust | Set |

- | | | |
|----|--------------|----------------|
| 8. | Landing Gear | DOWN, six down |
|----|--------------|----------------|
- Pilot checks gear lever in detent. Both pilots check that the gear warning light is out and that all six gear indicate down and locked.

- | | | |
|-----|----------------|--------------|
| 9. | Crosswind Crab | Set, checked |
| 10. | Target Trim | Noted |
| 11. | Landing Check | Completed |
- Gear
 - Flaps
 - Airbrakes 4 or as required
 - Lights
 - Fuel
- A check of the above items will be made when established on final.

DO NOT USE FOR FLIGHT**TAXI-BACK LANDING**

Full stop taxi-back landings may be accomplished under the following limitations:

1. Airplane gross weight will not exceed 270,000 pounds.
2. Touchdown will be accomplished in the first third of the existing runway to include the sterile portion of the approach end.
3. Planned landing ground run will not exceed 50% of the available runway exclusive of the sterile portion of the approach end.
4. After establishing a stable ground roll, brakes will be checked for operation followed by intermittent application of brakes as required.
5. A minimum interval of 15 minutes air time will be established between landings or prior to retracting the gear to provide wheel and brake cooling.
6. If the first taxi-back landing accomplished is:
 - a. Above 250,000 pounds, a maximum of one full stop taxi-back landing may be accomplished on each sortie, followed by a final full stop landing utilizing the drag chute,
 - b. At or below 250,000 pounds, a maximum of four full stop taxi-back landings may be accomplished on one sortie. The fourth landing may be followed by a final full stop landing utilizing drag chute.

TAXI-BACK LANDING CHECKLIST

- | | | |
|-----|---------------------|---------------------------------|
| 1. | Airbrakes | Position 6 |
| 2. | Drag Chute | Deploy (if required) |
| 3. | Brakes | Checked |
| 4. | Hydraulic System | Checked |
| 5. | Crosswind Crab | Centered |
| 8. | Drag Chute | JETTISON (if applicable) |
| 9. | Brakes | Set |
| 10. | Sliding Window | Open |
| 11. | Stabilizer Trim | Set Checked for takeoff setting |
| 12. | Airbrakes | OFF |
| 13. | Flaps | 100%, lever down |
| 14. | Fuel Panel Switches | Check |
| 15. | Takeoff Data | Reviewed |
| 16. | Crew | Stand by for takeoff |
| 17. | Lights | ON |

Turn landing, taxi, and crosswind landing lights on for night or day operations unless reflection reduces pilot visibility.

- | | | |
|-----|--------------------|-------------|
| 18. | Crosswind Crab | Set Checked |
| 19. | Takeoff Thrust | Set |
| 20. | 70 Knots | Now |
| 21. | Stabilizer Trim | Monitor |
| 22. | Unstick Speed (S2) | Now |

DO NOT USE FOR FLIGHT**AFTER LANDING**

The after-landing check shall be performed after the aircraft has been turned off the runway. Hard taxi braking or riding the brakes shall be avoided at all times, particularly after a landing or refused takeoff.

AFTER LANDING CHECKLIST

1. Lights OFF (if applicable)
Turn landing, taxi, and crosswind landing light switches OFF or as necessary for taxi operations.
2. Drag Chute Lever JETTISON
The drag chute will be jettisoned and the control handle returned to LOCKED by the pilot after the aircraft has turned off the runway and prior to being stopped for completion of the "After Landing Checklist."

CAUTION

- To prevent or minimize damage to aircraft structure as the drag chute disconnect link strikes it during the jettison sequence, jettison the chute at the lowest taxi speed that will keep the chute inflated.

3. Parking Brakes Set
4. Yaw Switch DISENGAGE
5. Rudder/Elevator Hydraulic Switches OFF
8. Airbrake Lever OFF
9. Stabilizer Trim Reset to zero
12. Starter Switches OFF
13. Unnecessary Electrical Equipment:
 - b. Mach Indicator Switch OFF
 - c. Pitot Heat Switches OFF
 - d. Windshield & Engine Anti-Icing Switches OFF
 - f. Autopilot Master Switch OFF
15. Generators 1, 7 OFF
16. Throttles 1, 2, 7, 8 75% rpm, then CLOSED

While taxiing back to the ramp, advance throttles 1, 2, 7, and 8 to approximately 75% rpm for not less than 15 nor more than 30 seconds before moving to the CLOSED position. This will insure complete scavenging of engine oil and prevent overservicing. This procedure will also prevent fuel from accumulating underneath the engines after shutdown. No. 5, 6 engines may also be shut down if necessary to reduce taxi speed and still maintain sufficient electrical and hydraulic power for the aircraft.

17. Fuel Panel Checked
Close all fuel valves not required.
18. Sliding Window Open
Open sliding window to relieve cabin pressure.
19. Bomb Door Switch (nuclear and training missions only) OPEN
If munitions are aboard or have been released, bomb doors will not be opened until after parking.

ENGINE SHUTDOWN**CAUTION**

- If an engine has been operating at above 85% rpm for a period exceeding 1 minute after landing, allow the engine to idle at least 5 minutes before shutting down. This will prevent damage resulting from rapid temperature change.
- Normally, an engine will be sufficiently cool after landing to permit an immediate shut

DO NOT USE FOR FLIGHT**BEFORE LEAVING AIRCRAFT CHECKLIST**

- | | | |
|----|-----------------------------------|------|
| 1. | Parking Brakes | Set |
| 2. | Anticollision & Navigation Lights | OFF |
| 3. | EVS Power Switches | OFF |
| 4. | Gyro Power Switch | OFF |
| 5. | Bomb Door Switch | OPEN |

Bomb doors will be opened at this time if conventional internal munitions were carried. Ground personnel will be on interphone and confirm that bomb doors are clear.

WARNING

- If conventional internal munitions were carried, the flight crew must visually check bomb bay prior to opening bomb doors.

- | | | |
|----|------------------|----------------------|
| 6. | Generators 3 & 5 | OFF |
| 7. | Throttles | 75% rpm, then CLOSED |

Before shutting down any engines, advance throttles to 75% rpm to accomplish scavenging. Sufficient engine scavenging will be accomplished by not less than 15 nor more than 30 seconds of engine operation at 75% rpm. Move throttle to CLOSED within a few seconds after retarding throttle from the 75% setting.

- | | | |
|-----|---------------------|--------------------|
| 8. | Radios | OFF |
| 9. | Fuel Panel Switches | OFF or CLOSED |
| 10. | Oxygen System | OFF |
| 11. | Parking Brakes | OFF |
| 12. | Light Switches | OFF or as required |
| 13. | Battery Switch | OFF |

SECTION II

ALL WEATHER OPERATION

INSTRUMENT FLIGHT PROCEDURES

The procedures and techniques outlined in current instrument flying directives should be followed. Flight characteristics during instrument conditions do not differ from those encountered during visual flight conditions. Limit angle of bank to 30° for all normal instrument maneuvers.

INSTRUMENT TAKEOFF AND INITIAL CLIMB

An instrument takeoff is essentially the same as a normal VFR takeoff. The same procedures are used. Ensure the attitude indicator is set for takeoff by aligning the horizon bar with the miniature aircraft.

1. Align the aircraft visually with the runway. The pilot will visually monitor the takeoff and initial climb. A takeoff with reference to instruments exclusively may be required because of low visibility conditions.

NOTE

- The bank steering bar will be used during the takeoff and climb as an aid in heading control. Cross-checking of the bank steering bar, turn needle, and heading indicator will provide indication of attitude indicator failure in the roll axis. If the roll axis of the ADI is inoperative on takeoff, the bank steering bar will aid in maintaining a wings-level attitude until a new heading is selected. This type of failure has occurred several times without a warning flag in view. If a new heading is selected, then the roll axis failure should become apparent as the turn is initiated. A rapidly precessing heading indicator will also give the same indications.
- As the aircraft breaks ground, maintain the unstick attitude as indicated by the attitude indicator until a cross-check of vertical velocity indicator and altimeter indicate a definite rate of climb with increasing airspeed.

WARNING

- If a pitchup occurs as the aircraft becomes airborne, failure to initiate positive action with the elevator control and trim to stop the aircraft nose up rotation could result in a stall.
- The OFF flag will not appear during every attitude indicator failure. Therefore, it is possible that a malfunction of the attitude indicator might be determined only by cross-checking it with the turn and slip indicator and the other flight instruments.

NOTE

- The ATT warning flag indicates the attitude information displayed on the pilot and/or pilot attitude director indicator may be erroneous and the standby attitude indicator should be checked to determine proper attitude references.
- An error in the pitch indication of the attitude indicators is generated during accelerations or decelerations. The error is indicated in a nose high direction during and after a forward acceleration and a nose down direction during and after deceleration. The longer the duration of acceleration (or deceleration), the greater will be the indicated error and the longer it will persist when acceleration (or deceleration) ceases. The erection system will reduce the error at about the same rate as it was generated. Pitch error may reach one bar width during a high gross weight takeoff.

3. Retract the gear as recommended for a VFR takeoff; however, be certain that a safe stabilized climb has been established. Adjust pitch as necessary to maintain a climb at 180 knots IAS.

4. Retract flaps as recommended in for a VFR takeoff.

DO NOT USE FOR FLIGHT**INSTRUMENT CRUISE**

The aircraft has satisfactory handling characteristics throughout the design airspeed and altitude range. Use the recommended procedures for cruise operation.

NOTE


- The rotating anti-collision lights should be turned off during actual instrument flight conditions whenever the pilot can notice the rotating light reflections in the cockpit. A pilot may experience vertigo from these reflections. In addition, the lights will be ineffective during such instrument flight conditions.

HOLDING

Enter the holding pattern in accordance with procedures as outlined in current directives. Establish a holding airspeed of 230 knots IAS for all altitudes from 15,000 to 35,000 feet and for all gross weights up to 325,000 pounds. Maintain the airspeed 10 knots above that given or Mach .77, whichever is less, for endurance at the given weight to allow for holding turns.

NOTE

- If it is necessary to endure and fuel quantity is low, establish the holding airspeed recommended for the existing gross weight and altitude. Increase the airspeed 10 knots or maintain Mach .77, whichever is less. Maximum endurance altitude is recommended.

DO NOT USE FOR FLIGHT**TYPICAL DESCENTS AND PENETRATIONS****NOTE**

- Enroute descents are compatible with the typical penetration procedures except for aircraft configuration, airspeed, rate of descent and routing to the final approach.

1. Prior to starting a penetration, initiate "Descent and Landing Checklist."

2. A normal penetration is accomplished with the gear down, throttles idle, airbrakes position 4 or as required at 240 knots IAS or .75 Mach, whichever is slower.

WARNING

- Care should be taken to retrim between each two-unit increment of airbrake operation.

DO NOT USE FOR FLIGHT

NOTE


- Rate of descent may be varied (by airbrake and/or throttle position) to satisfy local penetration procedures.
3. Conform to published procedures.
 4. Pilot obtains altimeter setting prior to descent and set altimeters at the prescribed time during descent.
 5. Retract airbrakes as required. Allow the aircraft to decelerate to 220 knots IAS. Complete the "Descent and Landing Checklist" as required. Establish best flare speed plus 30 knots. Reduce airspeed to best flare plus 10 knots prior to the final approach fix or glide slope interception. Maintain best flare plus 10 knots until the flare for landing is started. If visual references at the missed approached point are insufficient to land, execute the missed approach procedure.


DO NOT USE FOR FLIGHT

INSTRUMENT APPROACHES

This aircraft and all modified versions thereof are in approach category "E."

RADAR APPROACH



DO NOT USE FOR FLIGHT


Entry into the radar approach pattern is normally made with gear down at 220 knots IAS. Complete "Descent and Landing Checklist". Adjust power to maintain best flare speed plus 30 knots IAS after the flaps are down. Reduce airspeed to best flare plus 20 knots on base leg. After the turn to final approach and prior to reaching the glide slope, reduce airspeed to best flare plus 10 knots IAS. Maintain best flare plus 10 knots until the flare for landing is started. When the minimum altitude is reached as indicated by the altimeter or when advised by the controller, whichever occurs first, perform the missed approach procedure if visual references are inadequate for landing.

DO NOT USE FOR FLIGHT**AUTOMATIC ILS APPROACH**


The aircraft is equipped with an approach coupler which permits automatic ILS approaches. Except for the use of the autopilot and approach coupler, the following procedures also apply to manual approaches.

- 1** **TRANSITION TO FINAL** – Set the nav mode select switch to ILS, tune the ILS frequency, set the inbound course, complete the "Descent and Landing" or "Traffic Pattern Checklist" Establish best flare plus 30 knots IAS. Engage autopilot and "altitude hold."

- 3** When established on localizer course (CDI centered), engage the autopilot localizer and place the nav mode select switch to ILS APP. Stabilize aircraft at best flare plus 10 knots IAS. Eliminate localizer standoff by use of the roll trim knob.

**NOTE**

The attitude views displayed are shown for the ARU-28/A ADI on aircraft **Less BB**, but they are also the same attitude views for the ARU-49/A ADI on aircraft **BB**.




- 2** Decelerate to best flare plus 20 knots IAS. When within 90° of the localizer course, intercept the localizer course by keeping the bank steering bar centered.





DO NOT USE FOR FLIGHT


- 4 When the glide slope reaches center, engage glide slope switch. Adjust power to maintain best flare plus 10 knots IAS.



- 5 Maintain crosscheck of ADI and HSI. Maintain airspeed at best flare plus 10 knots.



- 6 Check trim indicators before disengaging autopilot. Disengage autopilot and accomplish landing or perform missed approach.

**TRANSITION TO FINAL**

Accomplish a normal transition as specified in the terminal charts. Set the NAV mode select switch to ILS, tune the ILS frequency, set the inbound localizer course in the course selector window. Complete the "Descent and Landing Checklist" and established best flare plus 30 knots IAS. Engage the autopilot and turn altitude control switch ON when at glide slope interception altitude. When the aircraft is within 90' of the inbound course, decelerate to best flare plus 20 knots IAS and center the bank steering bar. This will initially establish up to a 45° intercept to the localizer. As the aircraft approaches the localizer, the bank steering bar will direct a turn on course. When the aircraft is on the localizer course inbound (CDI centered), engage the autopilot localizer placing the nav mode select switch to ILS. Stabilize the aircraft at best flare plus 10 knots IAS prior to the glide slope interception point. Eliminate localizer standoff by use of the roll trim knob.

FINAL APPROACH

When the glide slope indicator reaches center, engage the glide slope placing the nav mode select switch to ILS APP and adjust power to maintain best flare plus 10 knots IAS. For a manual approach, keeping the bank steering bar centered will automatically correct for wind, and keeping the pitch steering bar centered will establish the pitch attitude necessary to correct to or maintain the glide slope. Continue the approach until visual references are sufficient to land or to published minimums, whichever is higher. At this point, disengage the autopilot to land or to follow the missed approach procedures. Check trim indicators prior to disengaging autopilot.

WARNING

- During an ILS final approach using the Flight Director System (ILS APP mode selected) the loss, or reduction in strength, of the glide slope signal will normally cause the glide slope warning flag to appear. Simultaneously with the warning flag appearance, the glide slope indicator and pitch steering bar may remain at or slowly move toward a centered position. Failure to immediately observe the (red) warning flag under conditions requiring high instrument (red) lighting intensities, coupled with the false "on glide slope" indication, could result in misinterpretation by the pilot. During the ILS final approach phase a frequent cross-check should be made for the glide slope warning flag and/ or unduly stabilized glide slope indicator/ pitch steering bar combination. A continuous cross-check of altitude and rate of descent should be made as well as monitoring marker beacons, aural signals and radar altimeters, whenever possible.

CIRCLING APPROACH

Generalized procedures for circling approaches are contained in current instrument flight directives. Follow enroute descent or jet penetration procedures; however, reduce airspeed to best flare plus twenty knots prior to the final approach fix. Maintain twenty knots above best flare speed during the circling maneuver until beginning rollout to align with the landing runway. At that time, reduce to best flare speed plus ten knots until the landing flare point is reached. Bank angle should be limited to thirty degrees throughout the maneuver.

MISSED APPROACH

Missed approaches are accomplished using the same procedures as for VFR go-arounds. Advance throttles as required, retract airbrakes, establish a positive climb (approximately 1000 feet per minute is appropriate for most missed approaches), trim as required, and check for a positive increase in airspeed. Aircraft acceleration upon executing the missed approach procedure is such that at light weights under instrument conditions flap placard speeds may be rather quickly exceeded.

WARNING

- Care should be exercised in applying power at light gross weights due to pitchup developing during acceleration.

Retract gear as soon as it is certain that the aircraft will not touch the ground and retract flaps as specified if the published missed approach procedure is to be followed or if proceeding to an alternate airport. During the flap retraction cycle, it is required that the pilot monitor the aircraft attitude indications as closely as possible, keeping the aircraft trimmed to a zero stick force, especially during the last 20% of flap retraction.

NOTE

- If a closed radar approach pattern is to be made, the pilot may, at his discretion, leave the gear and flaps down and maintain airspeeds as specified for a normal radar approach pattern.

DO NOT USE FOR FLIGHT

SIM OPS

We encourage you to visit the one-stop resource for the B-52 Driver flight sim operations: [the Sim Ops](#)

TECHNICAL SUPPORT

If you have trouble with the product, please use our [Support Section](#)

FORUM

You are invited to join [Captain Sim forum](#)

NETWORKS

Please join us at:

[Forum](#)

[Twitter](#)

[Facebook](#)

[YouTube](#)